Jammer of microphones and audio recordersSEL 08

SEL 08 is a small size portable microphone jammer for personal use that helps protect confidential audio information during conversations in indoor meetings, outdoors or inside the car. It can be easily and quickly installed inside a car, on or under a conference room table, or built into a briefcase or purse. Despite its small size, SEL 08 is a highly effective jamming device, producing a complex jamming signal in the ultrasonic band above the point of human hearing.

Array of 8 high quality ultrasonic transducers controlled by a microprocessor achieving the best possible jamming efficiency and making any microphone recorded speech signal unintelligible to listen to.





Application

Device effectively blocks wiretaps, voice recording and microphones in a distance from 0,5 to 4 meters such as:

- microphones in cell phones;
- digital recorders of the sound with the built-in microphone or the microphone on the cable;
- professional digital dictaphones of the type: EDIC-the mini, Gnome, Olympus, Papyrus...;
- dictaphones built-in in Smartphones of the type: iPHONE 15 PRO MAX, HTC, SONY, LG, SAMSUNG...;
- radio microphones, microphones of recorders audio-the video;
- microphones of cameras, bugging microphones;
- professional dictaphones hidden in cards to ATMs;

Features

- Type of work: proprietary software for generating digital ultrasonic jamming signal;
- The radio remote control turns on and off;
- Charging and battery status indicator;
- Quiet operation does not emit an audible and troublesome sound;
- Simple operation and use.

Specifications

Max range: depending on the type of voice recorder, wiretapping	0,5-4 meters
Directionality	horizontal and vertical planes 85°
Power supply	built-in internal accumulator Li-ion / the power supply 5V/110 230V
Maximum continuous operating time	4-5 hours, break time 30 minutes.
Battery life	4-5 hours
Charging time	3 hours
Remote control	switching on/off, the range ~20 meters
Wireless remote control	work frequency 433.92 MHz in the ISM band
Weight	0,5 kg,
Dimensions	20x12x4 cm
Operating temperature	0°+40°C (32-104 Fahrenheit)

